

# D3/E3 ALUMINIZED RADIANT HEAT JACKET

HS-18007-4585

### **PRODUCT DESCRIPTION**

D3/E3 Aluminized Radiant Heat Jacket is designed to protect against multiple hazards, shielding metallurgical workers from radiant heat, convective heat, and molten metal splashes. It enhances comfort and efficiency by providing non-restrictive, comfortable protection that helps workers perform better. OTEGO REFLESPACE® Aluminized Fabric has outstanding resistance to abrasion and delamination that gives better life expectancy of PPE.

#### **FEATURES & BENEFITS**

Stitched with para aramid thread

Stand-up collar design for enhanced neck protection

Front closure with concealed fasteners for a clean and secure fit

Straight-cut body for easy movement

Adjustable cuffs with hook-and-loop fasteners

#### PRODUCT DETAILS

FITS : Male COLOR : Silver

SIZE: L-5XL

SIZE	L	XL	2XL	3XL	4XL	5XL
Height	170	175	180	185	190	195
Body Chest	92	96	100	104	108	112
Center back length	76	78	80	82	84	86
Shoulder across	48.8	51	52.2	53.4	54.6	55.8
Sleeve length	64	65.5	67	68.5	70	71.5

#### **FABRIC SPECIFICATION**

Gram Weight: 515 gsm  $\pm$ 30





Front



#### CERTIFICATION

CODE	EN ISO 11612	RoHS	REACH
4585	✓	<b>✓</b>	✓



## INHERENTLY FLAME RESISTANT PPE THERMAL RADIATION PROTECTIVE WEAR

Base Cloth			Carbon-aramide
Width			1500mm(59 inches)
Aluminization			Reflespace® Technology
Tear Strength	NF EN ISO 4674-1	Warp	≥8 daN
rear Strength	NF EN 130 4014-1	Weft	≥9 daN
Thickness	NF EN ISO 2286-3		0.75 mm ±0.06
Folding	NF EN ISO 5981(1000g)	Warp	500 UN
rotaing		Weft	500 UN
Certification	NF EN ISO 11612		A1 B1 C3 D3 E3 F1





For more cleaning and maintenance instructions, please contact your sales to obtain.