



ABOUTBLU/ANATOMIC

PROFESSIONAL

EVO NAVY  
FRESH

51432 03LA

S1P  
ESD  
SRC  
DGUV 112-191  
EN ISO 20345:2011



**UPPER** Breathable perforated suede leather.

**LINING** **PLASMAFEEL** Lining in 3D fabric that keeps the foot constantly cool and dry thanks to the instantaneous absorption of sweat and its immediate dispersion outside of the shoe. Breathable, antibacterial, resistant to wear and abrasion.

**INSOLE** **TECH SOFT** Thermoformed. Runproof, multi-layered, antistatic latex-foam fabric, that is antibacterial, breathable and absorbent with anti-fungus activated carbons. Shock absorbing heel and plantar arch support.

**SOLE** **PU/PU DUAL DENSITY BASF PUR Elastopan®** polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Polyurethane outsole, with an elevated grip, resistant to wear, oils and hydrocarbons. System of energy absorption on the heel. It leaves no mark on the surface. **SATRA UK "Pedatron Test"** that certifies abrasion resistance three times greater than standard

**LAST** The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. The Anatomic sole, following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort

**TOE CAP** The **POWER CAP** is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules. Being metal-free it is undetectable by a metal detector, and helps to maintain a constant body temperature. It provides maximum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It exceeds the EN-ISO12568 requirements.

**MIDSOLE** **TEXON ENIGMA ZERO HT2** Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation. Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18

**ANTI-TORSION SUPPORT** **COMPOSHANK** Anti-torsion support in ABS. It is applied between the antiperforation midsole and the midsole, corresponding to the arch of the foot. It improves stability on ladders, where foot support is not complete.

**ANTI-STATIC DEVICE** **SILVER STRIP DISCHARGE (SSD)** Conductive cotton tape and silver threads inside the upper and in contact with the foot. It is an anti-static device that guarantees greater safety than the standard, increases the dispersive capacity of the electrostatic charges throughout the life of the shoes.

**WEIGHT SIZE 42** 580 gr

**SIZES** 35-49

#### TECH SOFT



#### FEATURES



#### PLUS



#### TECHNOLOGIES

