

D3/E3 ALUMINIZED THERMAL INSULATION COAT

HS-18001-5465

PRODUCT DESCRIPTION

D3/E3 Aluminized Thermal Insulation Coat is designed to protect against multiple hazards, shielding metallurgical workers from radiant heat, convective heat, and molten metal splashes. It enhances comfort and efficiency by providing non-restrictive, comfortable protection that helps workers perform better. OTEGO REFLESPACE® Aluminized Fabric

has outstanding resistance to abrasion and delamination that gives better life expectancy of PPE.

FEATURES & BENEFITS

Stitched with para aramid thread

Stand-up collar design for enhanced neck protection

Front closure with concealed fasteners for a clean and secure fit

Straight-cut body for easy movement

Adjustable cuffs with hook-and-loop fasteners

PRODUCT DETAILS

FITS: Male COLOR: Silver

SIZE : L-5XL

SIZE	L	XL	2XL	3XL	4XL	5XL
Height	170	175	180	185	190	195
Body Chest	92	96	100	104	108	112
Center back length	108	111	114	117	120	123
Shoulder across	47.6	48.8	50	51.2	52.4	53.6
Sleeve length	62	63.5	65	66.5	68	9.5







Side

FABRIC SPECIFICATION

Gram Weight: 350 gsm \pm 30

CERTIFICATION

CODE	EN ISO 11612	RoHS	REACH
5465	✓	√	✓



INHERENTLY FLAME RESISTANT PPE THERMAL RADIATION PROTECTIVE WEAR

Base Cloth			Carbon-aramide
Width			1500mm(59 inches)
Aluminization			Reflespace® Technology
Tour Strongth	NF EN ISO 4674-1	Warp	≥5 daN
Tear Strength		Weft	≥5 daN
Thickness	NF EN ISO 2286-3		0.48 mm ±0.03
Folding	NE EN ISO E001/1000a)	Warp	500 UN
rotating	NF EN ISO 5981(1000g)	Weft	500 UN
Certification	NF EN ISO 11612		A1 B1 C3 D3 E3 F0





For more cleaning and maintenance instructions, please contact your sales to obtain.