



ABOUTBLU/ANATOMIC

SAFE KNIT

LE MANS NAVY

50376 02LA


S3L FO SR ESD
DGUV 112-191
EN ISO 20345:2022

UPPER	Water-repellent and breathable polyester jacquard fabric. Cut resistant, anti-fraying, rip and abrasion resistant. Anti-abrasion scuff-cap. Normal laces extra
LINING	PLASMAFEEL Lining in 3D fabric that keeps the foot constantly cool and dry thanks to the instantaneous absorption of sweat and its immediate dispersion outside of the shoe. Breathable, antibacterial, resistant to wear and abrasion.
INSOLE	TECHSOFT Thermoformed. Runproof, multi-layered, antistatic latex-foam fabric, that is antibacterial, breathable and absorbent with anti-fungus activated carbons. Shock absorbing heel and plantar arch support.
SOLE	PU / TPU BASF PUR Elastopan® polyurethane foam insole, ensures the maximum comfort and the absorption of the impact on all surfaces. Bi-colored TPU outsole, with an elevated grip, resistant to wear, oils and hydrocarbons. System of energy absorption on the heel.
LAST	ANATOMIC SOLE The anatomical shape of the injected sole, unlike removable insoles, is inalterable for the entire lifetime of the shoe. The Anatomic sole, following the natural morphology of the foot, provides a natural support to all its points, ensuring maximum comfort
TOE CAP	POWER CAP is in multilayer fiberglass and rubber particulate. It stands out for its robustness and lightness, guaranteeing a shock absorption up to a max. 200 Joules. Being metal-free is undetectable by a metal detector, and helps to maintain a constant body temperature. It provides maximum safety even at extreme temperatures above and below zero, providing a thermal insulation that is better than aluminum or steel toe-caps. It is compliant with CSA Canada regulations and exceeds the EN-ISO12568 requirements.
MIDSOLE	TEXON ENIGMA ZERO HT2 Non-metallic antistatic, flexible, anti-perforation fabric insole, built with several layers of high-tenacity fibres. It ensures perfect thermal insulation Compliant with: EN 12568:2012; EN ISO 20344/345; CSA-Z195-14; ASTM F2413-18
ANTI-TORSION SUPPORT	COMPOSHANK Anti-torsion rigid ABS support. It is applied between the anti-perforation midsole and midsole, at the arch of the foot. It improves stability on stairs, where the support of the foot is not ideal
ANTI-STATIC DEVICE	SILVER STRIP DISCHARGE (SSD) Conductive cotton tape with silver threads, positioned inside the upper and in direct contact with the foot. It is an extra Anti-static device, increasing and stabilizing the dispersive capacity throughout the life of the shoe.
WEIGHT SIZE 42 580 gr	SIZE 35-49

TECH SOFT



FEATURES



PLUS



TECHNOLOGIES

